STILETTO END CAPS for ISO GRIPS   6249

PARTS INCLUDED

2	Stiletto End Caps
8	#4–40 X 9/16" Socket Head Cap Screws — Stainless Steel
8	#4–40 x 3/4" Socket Head Cap Screws — Stainless Steel
1	Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.

ATTENTION! **This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.**

TOOLS SUGGESTED
Set of Hex Wrenches

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

STEP 1   Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition.

STEP 2   Remove the original ends from the ISO-Grips.

STEP 3   Remove the trim rings from the original end caps and place them on the new Stiletto End Caps.

STEP 4   Install a Stiletto End Cap and trim ring assembly on each ISO-Grip using four #4–40 x 9/16" Socket Head Cap Screws. For ISO-Grips equipped with an ISO Throttle Boss, we have included longer (3/4") #4–40 Socket Head Cap Screws.

ATTENTION! **It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Küryakyn will not issue a warranty on components lost due to improper installation. Periodic maintenance may be required.**