



Mounting Suggestions Yamaha V-Star 1100 Classic 2000-2009 & Silverado 2002-2009 Two-Piece Seat

Tools Required:
• Metric Wrenches

Hardware:
• White Nylon Washer (Included)



Baseplate Features:

The two-piece, marine-grade fiberglass baseplate directly replaces the stock two-piece seat. Rubber bumpers are positioned to prevent the seat from touching the frame and fender.

Stock Seat Removal Steps

1. Remove 8 mm screw from fender.
2. Slide passenger seat back to remove.
3. Remove 8 mm screw behind solo.
4. Slide solo back and up to remove.

Mounting of Mustang Seat

1. Slide nose bracket on front of solo into receiver at base of gas tank.
2. Secure rear of solo to fender with stock 8 mm screw.
3. Slide bracket on front of passenger seat under fender bracket.
4. Secure rear of passenger seat to fender with stock 8 mm screw. On models with 8 mm stud, put white washer between fender and the seat's rear chrome triangle and secure with stock cap nut.

Enjoy the comfort of your new Mustang Seat!



These steps are guidelines to help you install your new Mustang product. If you need further assistance, please call us at 800-243-1392, Monday through Friday 9:00 - 5:30 Eastern, or send an email to questions@mustangseats.com, or visit our website at www.mustangseats.com.

For care and maintenance of our seats, please go to our website under "Support".

Ref part #75910, 75912, 79240, 79242