Commuter Lite and Sport Tank Bags Mounting Instructions

CL-1100-R and CL-1

Please read instructions carefully before installation. We recommend this product be installed by a qualified, and experienced technician. If you are unsure of any of the below directions and or your ability to correctly and securely install the product, please contact us or your local dealer for help. Below diagrams show typical installation, your vehicle may be different so please use diagrams as a guide. Make sure your vehicle is clean and free from dirt, road grime etc. where this product mounts. It is the niders responsibility to make sure the product is mounted and secure before each use. Loading the bag may result in a change of position, always check for proper mounting position after loading and before ei and every ride. Always store heavier items in the bottom of the bag for better weight distribution and balance. Clean the mounting surface with a soft towel before installing the tank bag. The Commuter series tank bags are versatile and unique in the fact that they include both magnetic and strap mounts to be able to fit all types of motorcycles.


For metal tanks, untuck the magnetic flaps from under the base and hold against bag while gently positioning the bag on the gas tank. Once in place, slowly lower each flap on the tank to secure the bag. When removing or repositioning your bag, each flap must be lifted off the tank first, do not drag the bag off or over the bike. This will help prevent any scratching or tipping the bike over. Please do not leave the tank bag on your motorcycle when not in use.



You should hear a snap ensuring proper placement and connectivity. Once secure pull the strap snug ensuring that the bag is resting on a flat surface and has little to no movement. Any extra strap can be folded and tucked inside the provided elastic loops



For motorcycles with plastic or aluminum tanks you must use the strap mounting system. For the front of the bag, use "Strap A" with 2 male buckles on either end. Remove one male buckle from the elastic strap keeper and and loop around the frame or steering head behind the triple clamp making sure the strap is not pinched by the steering stops or displacing control cables or hoses.



To install the rain cover, align the cover so the barrel clasp is closest to you while riding. Place the cover over the bag and unfold the two side magnetic flaps and feed through the elastic bands on the cover. If using strap mounting system, simply tuck the magnetic flaps back into the base



Warning


Read the installation instructions and make yourself amiliar with the process of installing the Nelson Rigg products(s) on your vehicle. It is your responsibility to install the product(s) correctly and securely as outlined in these instructions. Rigg Gear products must not be overladed or over tightened. Failure to adhere to these vernings may result in, but not limited to the product becoming detached, becoming langled in moving parts of the vehicle, unstable vehicle dynamics, reduction in the ab to control the vehicle. The result(s) could lead to serious injury.

Always drive safely. Always were a helmet and protective apparel.

Now feed the buckle back through the strap holder. Adjust both strap lengths so the clips lay on the front of the fuel tank just behind the triple clamp. Now untuck the female buckles from under the base and align the bag on the tank and clip male buckles into female buckle on tank bag.




To secure the rear of the bag, use single " B" with the male buckle on one side and k the opposite side. Remove from the strap keeper and pass the loop around a part of frame or similar solid bike part, then push the male buckle through the loop and to securely attach. Feed the strap through strap holder and connect the male buckle of the female buckles on the tank bag. Re on other side




Parts Included For Mounting

Strap A Strap with 2 male buckles



Strap B



3518 W. Lake Center Dr Ste A, Santa Ana, CA 92704 Tel (714)850-1811 Fax (714)850-1848 e-mail: info@nelsonrigg.com www.nelsonrigg.com

