



INSTALLATION

REPLACEMENT CLEVIS

4568

FOR KURYAKYN OFFSETS

FITS: KURYAKYN LONGHORN OFFSETS AND FOOTPEG OFFSETS WITH A CONICAL MOUNT CLEVIS, UPPER SHOCK MOUNTS (P/N 7973) AND UNDER SEAT PEG MOUNTS FOR SOFTAIL (P/N 7959, 7960, 7995 AND 7997).

PARTS INCLUDED

- 1 Clevis
- 1 3/8-16 x 1 Socket Head Cap Screw (SHCS)
- 1 5/16-18 x 7/8 Socket Head Cap Screw (SHCS)
- 1 5/16 Lock Washer
- 1 "D" Washer
- 1 Anti-Seize Packet
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KURYAKYN!

CAUTION! Ensure that the installation of this product does not interfere with the proper operation of the motorcycle before riding.

ATTENTION! It is the installer's responsibility to ensure all fasteners (including pre-assembled) are tightened before operation of the motorcycle. Kuryakyn will not warranty components lost due to improper installation. Periodic maintenance may be required.

ATTENTION! Ensure that the supplied anti-seize is applied to all threaded fasteners before installation; this will make future removal of the fasteners easier.

ATTENTION! Use the supplied anti-seize for any chrome-to-chrome fasteners; this will prevent galling and make future removal of fasteners easier.

TOOLS SUGGESTED

Set of hex wrenches

PROCEDURE

STEP 1 Park the motorcycle on a hard, level surface; turn off the ignition and allow the engine to cool.

STEP 2 Remove your footrest; save the hardware, it will be reused.

STEP 3 Remove old clevis; it will not be reused.

STEP 4 Install the new clevis; leave the fasteners loose until you have installed your footrest and adjusted the clevis.

STEP 5 Install your footrest.

-cont.-

CUSTOMER SERVICE

877.370.3604 (toll free)

INSTALLATION QUESTIONS

techsupport@kuryakyn.com
or call 715.247.2983

LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

· Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).

· The product must be properly installed, maintained and operated under normal conditions.

· Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.

· Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.

· Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.

· Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Kuryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.

· Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

ABOUT OUR CATALOG

You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today—select the "CATALOGS" icon. Each Kuryakyn product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Kuryakyn products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA All Rights reserved.



STEP 6 Adjust for comfort and clearance then tighten the fastener shown in PIC.1

NOTE Tightening the fastener shown in PIC.1 will positively engage the splines (shown in red).

STEP 7 Tighten all of the fasteners and ensure proper clearance and operation before riding the motorcycle.

Ride On!

PIC.1

