



# INSTALLATION

## ISO BOARDS with SPLINED BRACKETS 7916

### PARTS INCLUDED

- 1 Left Footboard Mount Assembly
- 1 Right Footboard Mount Assembly
- 1 Hardware Kit Includes:
  - 2 5/16"-18 X 7/8" Socket Head Cap Screw
  - 1 Anti-Seize
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

### THANK YOU FOR CHOOSING KÜRYAKYN!

**IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.**

**WARNING!** THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

**ATTENTION!** This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

**CAUTION!** This indication alerts you to the fact that ignoring the contents described herein can result in potential injury or material damage.

### TOOLS SUGGESTED

Set of Hex Wrenches

**STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.**

**STEP 1** Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition.

**WARNING!** YOU WILL BE WORKING AROUND THE ENGINE AND EXHAUST SYSTEM DURING INSTALLATION. ENSURE THAT THE ENGINE AND EXHAUST SYSTEM HAVE FULLY COOLED TO PREVENT INJURY.

**CAUTION!** These boards are not intended as a step. Passenger and rider should be aware that they should be used as a footrest only.

**NOTE:** Fits various applications, requires splined adapter mount, sold separately.

-cont.-

7916-21MC-0911

### CUSTOMER SERVICE

877.370.3604 (toll free)

### INSTALLATION QUESTIONS

techsupport@kuryakyn.com  
or call 715.247.2983

### LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
  - The product must be properly installed, maintained and operated under normal conditions.
  - Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
  - Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
- Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'S contained in components of Kuryakyn products will be warranted for defects in materials and workmanship for 3 years from the date of purchase where as all other components shall be warranted for one(1) year. This includes, but is not limited to; control modules, wiring, chrome & other components.
- Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

### ABOUT OUR CATALOG

For purchasing Kuryakyn® products, you can receive a complete catalog free of charge. Send the Proof-of-Purchase below with your address to: Kuryakyn, P.O. Box 339, Somerset, WI 54025, Please indicate either Accessories Catalog for Harley-Davidson® or GL & Metric Cruisers.

Be sure to ask your local dealer about other Kuryakyn® products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA® All Rights reserved.



kuryakyn.com


**NOTE:** This product should not be installed in place of a footpeg on a peg mount secured with a single fastener and no anti-rotation mechanism. This product will apply too much force and loosen the mount from the bike.

**STEP 2** Remove the OEM pegs from the bike.

**STEP 3** Separate the footboard from the mount by removing the 3/8"-16" socket head cap screw from the wide end of the board and the 1/4"-20" socket head cap screw from the narrow end. Be very careful not to lose the detent ball and spring located between the board and mount. See PIC.1.



**STEP 4** Loosely attach your adapter (sold separately) to the footboard mount with the 5/16"-18 X 7/8" Socket Head Cap Screw provided as shown in PIC.2. Shown is the splined adapter, Küryakyn P/N 8813 for Kawasaki. Your adapter may look slightly different but must have the splines on the inner face of the adapter to properly mate with the splines on the footboard bracket.



**ATTENTION!** Ensure that the supplied anti-seize is applied to all threaded fasteners before installation; this will make future removal of the fasteners easier.

**STEP 5** Mount the adapter to the bike using the OEM peg mounting hardware. Determine the angle that will provide you the most comfort without interfering with other nearby components. Fully tighten the 5/16"-18 X 7/8" Socket Head Cap Screw securing the footboard mount to the adapter.

**CAUTION!** Ensure that the installation of this product does not interfere with the proper operation of the motorcycle before riding.

**STEP 6** Place a dab of grease in the recess where the detent ball seats in the footboard mount to help hold it in place during reassembly. Attach the footboard to the footboard mount in reverse order as they were disassembled in STEP 3.

**ATTENTION!** It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Küryakyn will not issue a warranty on components lost due to improper installation. Periodic maintenance may be required.